

Application for URBAN DESIGN COMMITTEE Review

Department of Planning and Development Review Planning & Preservation Division 900 E. Broad Street, Room 510 Richmond, Virginia 23219 (804) 646-6335

http://www.richmondgov.com/CommitteeUrbanDesign

Application Type ✓ Addition/Alteration to Existing Structure ☐ New Construction ☐ Streetscape ☐ Site Amenity	Encroachment Master Plan Sign Other	Review Type ☐ Conceptual ☑ Final
Project Name: Belmont Road Roundabout		
Project Address: Belmont Road and West Belmont Ro		
Brief Project Description (this is not a replacement of one lane roundabout at the intersection of Belmont Road	id and West Belmont Road	The improvements will provide an
ermance and safer gateway to the neighborhood, reducir	ng neighborhood speeding a	and enhancing overall community
livability. Please see plans for the details.		Original Community
Applicant Information (on all applications other than encroachments, a City agency Name: Michael B. Sawyer, P.E.	representative must be the ap	oplicant)
City Agency: DPW - Transportation Engineering Division	Phono:	804-646-3435
Address: 900 E Broad street, Room 707, Richmond, VA	23219	VI
Main Contact (if different from Applicant): Maritza Fo		4 mg Itilione
Company: DPW - Transportation Engineering Division		804-646-6334
Email: Maritza.reyes@richmondgov.com	. none.	
Submittal Deadlines		

All applications and support materials must be filed no later than 21 days prior to the scheduled meeting of the Urban Design Committee (UDC). Please see the schedule on page 3 as actual deadlines are adjusted due to City holidays. Late or incomplete submissions will be deferred to the next meeting.

Filing

Applications can be mailed or delivered to the attention of "Urban Design Committee" at the address listed at the top of this page. It is important that the applicant discuss the proposal with appropriate City agencies, Zoning Administration staff, and area civic associations and residents prior to filing the application with the UDC.

UDC Background

The UDC is a ten member committee created by City Council in 1968 whose purpose is to advise the City Planning Commission on the design of projects on City property or right-of-way. The UDC provides advice of an aesthetic nature in connection with the performance of the duties of the Commission under Sections 17.05, 17.06 and 17.07 of the City Charter. The UDC also advises the Department of Public Works in regards to private encroachments in the public right-of-way.

Traffic Control Improvements – Belmont Road Roundabout

This project consists of the installation of one (1) roundabout at the existing intersection of Belmont Road, S. Belmont Road and W. Belmont Road. Belmont Road and S. Belmont Road are four lane divided streets with curb and gutter. W. Belmont Road is a two lane street with shoulders and ditches. The W. Belmont Road is controlled by stop signs and the S. Belmont Road is free-flow.

A 2011 traffic study was performed and determined a traffic signal was not warranted. At this time northbound direction intersection sight distance was improved and intersection ahead warning signs with 25mph advisory signs and hazard identification beacons were installed. Neighborhood meetings followed later and a roundabout was recommended by the City Transportation Engineer.

The roundabout is estimated to cost \$675,000. Design is 90% complete and construction is scheduled between July and October 2016. The design will require the acquisition of two small easements from two different parcels. The project will connect existing concrete sidewalks with similar materials. No on street parking loss is proposed.

The project as envisioned will include: "Mary Nell Holly", "Carissa Holly", "Dwarf Buford" and Blue Pacific Juniper" trees/shrubs; "Daffodil" and "Daylily" bulbs/perennials; and "Blue Pacific" ground covers inside the center roundabout.

The new roundabout will provide a traffic calming measure for all approach legs. These improvements will enhance driver, bicycle and pedestrian safety, while contributing to the beautification through new landscaping, and thereby enhancing the quality of life for our residents.


Below are our response to UDC/PC recommendations:

- (1) That the applicant consider reducing the apron width, with the excess used to enlarge the central landscaped island. The central landscaped island has been increased by 7' from that which was shown at the preliminary meeting. The inside radius increased from 16' to 24' which allows for more area for vegetation and planting.
- (2) That the final plans include a landscape plan and schedule showing plant species, quantity, location and size at the time of installation. The final plans include a landscape plan and schedule showing plant species, quantity, location and size as requested (sheets 6(1) thru 6(3).
- (3) That the applicant considers proving a larger shade tree (or multiple smaller trees) in the central landscaped portion of the roundabout in addition to the concentric rings of evergreen hedge, perennials/bulbs and an evergreen ground cover. We considered utilizing larger shade trees in the central island portion of the roundabout in addition to the concentric rings of plantings as requested but determined that we would conflict with the existing underground utilities (city gas line, city sanitary sewer line, and city waterline) and the existing overhead (Dominion Virginia Power line).
- (4) That the applicant continues the existing median tree planting on Belmont Rd in the new median extensions. The current plans do provide for additional green space within the extended median areas along Belmont Road which would be conducive for additional tree planting as requested. The current budget does not allow for additional tree plantings in the median extensions at this time, however the city has applied for additional funds and should those additional funds be allocated to the project, we would suggest that we consult with the city's urban forestry group to include additional trees.

- (5) That the applicant provides shade trees in the newly created, larger planting strips on Belmont Rd. The current plans do provide for additional green space within the curb extension areas along Belmont Road which would be conducive for additional tree planting as requested. The current budget does not allow for additional tree plantings in the curb extensions at this time, however the city has applied for additional funds and should those additional funds be allocated to the project, we would suggest that we consult with the city's urban forestry group to include additional trees.
- (6) That the applicant landscapes the splitters on W Belmont Rd. We have removed the plain concrete splitter islands at the noses of the new splitter islands as requested. These plantings are shown on the landscape plan.
- (7) That the applicant explores overhead utility relocation through the on the intersection to allow for larger tree species in the central landscaped island. We have designed the intersection layout to avoid having to move the Dominion Virginia Power poles (thus associated overhead lines). This was done to keep the cost to a minimum and avoid the schedule and budget complications associated with moving the line. In the event that the city would like to move the line for aesthetics or other reason, it could require additional easements, most assuredly would add cost to the project, and would require time for Dominion Virginia Power to order materials and schedule a crew.
- (8) That the final plans include lighting plan, showing make, model and finish for any light pole and fixture, as well as fixture light source and color. These final plans include a lighting plan (sheet 7) as requested. Plan includes the requested information (wooden poles with a 5'-7' arm with American Electric Lighting Roadway series 115 (250 Watt high pressure sodium luminaries)).
- (9) That the final plans include a signage plan. These final plans include a signage plan (sheets 2K(1) and 2K(2)) as requested.
- (10) That the applicant consider working with the Public Art Commission on an installation in the landscaped island. This items has been sent the information to the Public Art Commission. It should be noted that if the Public Art Commission does add a feature to the central island that the landscape plan would need to be modified to work in conjunction with the feature(s) envisioned.
- (11)That the applicant work with Mr. Nicholas Smith, a citizen who spoke to the item, to improve bicycle access around the roundabout. The applicant has met with and discussed the project with Mr. Nicholas Smith and has modified the design to include a dis-mount (coming into the roundabout areas) ramp and a re-mount (leaving the roundabout areas) ramp both north and south along Belmont Road as discussed and agreed upon.




TIMMONS GROUP



BELMONT ROAD AT WEST BELMONT ROAD ROUNDABOUT

DECEMBER 5, 2015
URBAN DESIGN COMMITTEE
MEETING

WWW.TIMMONS.COM 1






LANDSCAPE PLAN





AERIAL VIEW OF THE INTERSECTION








PROJECT FOOTPRINT FEATURES

- INTERSECTION CONTROL
- CENTER ISLAND
- TRUCK APRON
- CONCRETE SIDEWALK
- LANDSCAPE







AUTOTURN FOR WB-50 VEHICLE



CITY OF RICHMOND, VIRGINIA DEPARTMENT OF PUBLIC WORKS TRANSPORTATION ENGINEERING DIVISION

90% CONSTRUCTION PLANS

NOT FOR CONSTRUCTION



BELMONT ROAD ROUNDABOUT

(INTERSECTION OF BELMONT ROAD, SOUTH BELMONT ROAD,

& WEST BELMONT ROAD)

INDEX OF SHEETS

SHEET	NUMBER
COVER SHEET ALIGNMENT & SURVEY DATA SHEET RIGHT OF WAY DATA SHEET TRAFFIC MANAGEMENT PLAN MAINTENANCE OF TRAFFIC - DETOUR PLAN MAINTENANCE OF TRAFFIC - PHASES I - III GENERAL CONSTRUCTION NOTES TYPICAL SECTIONS CONSTRUCTION DETAIL SHEETS ROUNDABOUT GEOMETRY PLAN ROUNDABOUT GRADING PLAN EROSION & SEDIMENT CONTROL NOTES & DETAILS EROSION & SEDIMENT CONTROL PLANS DRAINAGE AREA MAP PAVEMENT MARKING & SIGNING PLAN ESTIMATE QUANTITY SUMMARY PLAN SHEETS PROFILE SHEETS ENTRANCE PROFILES RIGHT OF WAY PLAN SHEETS DRAINAGE DESCRIPTIONS & STORM SEWER PROFILES LANDSCAPE PLANS	1 1A 1B 1C(1) 1C(2) 1C(3) - 1C(5) 2 2A - 2B 2C(1) - 2C(3) 2D - 2E 2F - 2G 2H(1) - 2H(2) 2H(3) - 2H(4) 2J 2K(1) - 2K(2) 2L 3 - 4 3A - 3B 4A 3RW - 4RW 5 6(1) - 6(3)
LIGHTING PLAN	7

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED **NECESSARY BY THE CITY OF RICHMOND.**

XS-1 - XS-4

THIS PROJECT IS TO BE CONSTRUCTED IN ACCORDANCE WITH THE LATEST VERSIONS OF VDOT'S 2016 ROAD AND BRIDGE SPECIFICATIONS, 2008 ROAD AND BRIDGE STANDARDS, 2011 WORK AREA PROTECTION MANUAL, THE LATEST VERSION OF THE MUTCD AND AS AMENDED BY THE CONTRACT PROVISIONS.

CITY OF RICHMOND

AP	PROVED FOR RIGHT OF WAY
DATE	PROJECT MANAGER
DATE	CUDVEVC CUDEDINTINDENT
DATE	SURVEYS SUPERINTINDENT
DATE	MAINTENANCE ENGINEER
DATE	CITY TRANSPORTATION ENGINEER
DATE	CAPITAL PROJECTS ADMINISTRATOR
DATE	CITY ENGINEER
DATE	DIRECTOR OF PUBLIC WORKS

CITY OF RICHMOND

FUNCTIONAL CLASSIFICATION AND TRAFFIC DATA

ADT (2014)

ADT (2034)

ADT (2014)

D (%) (design hour)

T (%) (design hour)

D (%) (design hour)

T (%) (design hour)

WEST BELMONT ROAD

GS-7 MAJOR COLLECTOR

SOUTH BELMONT ROAD

GS-8 LOCAL STREET

25 mph

25 MPH MINIMUM DESIGN SPEED

BELMONT ROAD

GS-6 MINOR ARTERIAL

35 MPH MINIMUM DESIGN SPEED

35 mph

D (%) (design hour)

T (%) (design hour)

APPROVED FOR CONSTRUCTION						
DATE	PROJECT MANAGER					
DATE	SURVEYS SUPERINTINDENT					
DATE	MAINTENANCE ENGINEER					
DATE	CITY TRANSPORTATION ENGINEER					
DATE	CAPITAL PROJECTS ADMINISTRATOR					
DATE	CITY ENGINEER					
DATE	DIRECTOR OF PUBLIC WORKS					

REVISIONS

	NO.	DATE	COMMENTS
L			

DESIGN: M. FLEMING CHECKED: C. KIEFER APPROVED:

CITY OF RICHMOND BELMONT ROAD ROUNDABOUT

BELMONT ROAD, SOUTH BELMONT ROAD, & WEST BELMONT ROAD

DRAWING NO. SCALE 11/06/15 1" = 2000'0-28661 SHEET NO.

RÎCHMOND	
RGINIA®	

CIP#: 040-290-8910-102656-500552

VICINITY MAP SCALE: 1"=2,000'

11/06/15

REVISIONS:

CROSS SECTION SHEETS

DENOTES PROJECT

TIMMONS GROUP .***


YOUR VISION ACHIEVED THROUGH OURS.

1001 Boulders Pkwy., Suite 300 | Richmond, VA 23225

TEL 804.200.6500 FAX 804.560.1016 www.timmons.com

LOCATION

CIP-040-290-8910-102656-500552



RIGHT OF WAY DATA SHEET

					AREA										
			50.57									EASEMENTS			PROFFERS
PARCEL	LANDOWNER	TAX PARCEL ID	SQ. FT (DO NOT	SHEET NO.	TOTAL	FEE TAKING	PRESCRIPTIVE	FEE REMAINDER		PERMA	ANENT		TEMF	PORARY	
NO.	NO.	USE)	101/12	7 22 17 11 11 10	R/W		DRAINAGE	DRAINAGE & SLOPE	SLOPE	SIGHT DISTANCE	ENTRANCE RECONSTRUCTION	CONSTRUCTION			
					ACRES	ACRES	ACRES	ACRES	ACRES	ACRES	ACRES	ACRES	ACRES	ACRES	YES/NO
001	WESLEY MORRIS	C0081020004		03	1.560	0.000	0.000	1.560	-	-	-	-	-	0.013	NO
002	VALERIE JEREMIJENKO	C0080939032		03	2.513	0.000	0.000	2.513	-	-	0.013	-	-	0.017	NO

TIMMONS GROUP .****

3. Ordinance Number<u>N/A</u> 4. Adopted N/A 5. Accepted N/A REFERENCES

Technical Administrative Marvin Anderson Surveys Superintender Chris Kiefer (Timmons Group) Lamont L. Benjamin Capital Project Administrator

Deputy Director for
Transportation / Public Works Maritza Feliz-Reyes (DPW) Kenneth D. Horak Bobby Vincent Jr. Emmanuel O. Adediran Michael B. Sawyer City Traffic Engineer Director of Public Works DEPARTMENT OF PUBLIC WORKS RICHMOND, VIRGINIA

RIGHT OF WAY DATA SHEET

DESIGN BY: M. FLEMING REVIEWED BY DRAWN BY: M. FLEMING CHECKED BY: C. KIEFER FIELD NOTES
FB-XX, pp XX-XX SCALE HORIZ. N/A VERT. —

1B 11/06/15

2. THE WORK ZONE SHALL BE MAINTAINED ACCORDING TO THE CITY'S DEPARTMENT OF PUBLIC WORKS SPECIAL PROVISIONS AND THE 2011 VIRGINIA WORK AREA PROTECTION MANUAL. SPECIFICALLY, THE FOLLOWING 2011 VA WAPM TRAFFIC CONTROL SPECIFICATIONS OR A COMBINATION OF SUCH WILL BE USED REGULARLY:

2.1. TYPICAL TRAFFIC CONTROL (TTC) STATIONARY OPERATION ON SHOULDER (FIGURE TTC-4.1)

TTC SHOULDER OPERATION WITH MINOR ENCROACHMENT (FIGURE

2.3. TTC FLAGGING OPERATION ON A SINGLE LANE ROUNDABOUT (FIGURE

TTC ROAD CLOSURE OPERATION WITH A DETOUR (FIGURE TTC-48.1)

TTC SIGNING FOR PROJECT LIMITS (FIGURE TTC-53.0)

NOTE: THIS OPERATION IS IN A LOW-TRAFFIC, URBAN SETTING, THE TTO FIGURES ABOVE ARE FOR REFERENCE ONLY. ANY COMBINATION OF THE ABOVE OR TTC'S NOT LISTED ABOVE MAY BE NECESSARY. DETOUR SIGNS AS SHOWN IN FIGURE TTC-48.0 MAY BE OMITTED AT THE DIRECTION OF THE ENGINEER. THE CONTRACTOR SHALL INSTALL ALL NECESSARY SIGNS. MARKINGS. DELINEATORS OR OTHER TRAFFIC CONTROL DEVICES IN ACCORDANCE WITH THE CITY'S DPU SPECIAL PROVISIONS AND THE 2011 VA WAPM.

3. THE CONTRACTOR WILL MAKE ARRANGEMENTS TO STORE EQUIPMENT AND MATERIALS ON-SITE.

4. A PUBLIC COMMUNICATIONS PLAN IS NOT APPLICABLE TO THIS PROJECT ALTHOUGH PLANNED LANE CLOSURES SHALL BE ANNOUNCED TO THE ADJACENT LAND OWNERS.

TRANSPORTATION **OPERATIONS PLAN**

1. THE CONTRACTOR MUST ADVISE EMERGENCY COMMUNICATIONS AT 646-5700 OF THE CITY ON ALL PLANNED LANE CLOSURES 24 HOURS IN ADVANCE.

2. TRAFFIC INCIDENTS THAT MAY OCCUR IN THE WORK ZONE:

SURVE SUPER DESIGN

2.1. INSPECTOR SHALL NOTIFY ENGINEER OF THE TRAFFIC INCIDENT AND TAKE PICTURES OF THE WORK ZONE SETUP.

CONTRACTOR MAY HAVE TO SHUT DOWN THE WORK DEPENDING UPON THE INCIDENT SEVERITY

2.3. THE CITY POLICE WILL DETERMINE THE RESPONSE NECESSARY TO ALLOW TRAVELING PUBLIC AROUND INCIDENT, TAKE CONTROL OF THE INCIDENT, AND DIRECT ITS CLEARING AND RESTORATION TO NORMAL TRAFFIC CONDITIONS.

3. THE CITY POLICE INCIDENT REPORT WILL BE REVIEWED BY THE ENGINEER TO DETERMINE ANY NEEDED MODIFICATIONS TO THE WORK ZONE LAYOUT. IF CHANGES ARE NECESSARY THEN A MEETING WILL BE CALLED WITH THE CONTRACTOR, CITY INSPECTOR AND THE ENGINEER TO DISCUSS MODIFICATION AND IMPLEMENTATION OF AN IMPROVED TRAFFIC CONTROL PLAN.

4. ALL LANE CLOSURES AND STOPPING OF TRAFFIC FOR LONGER THAN FIVE MINUTES SHALL BE COORDINATED WITH THE ENGINEER, CITY OF RICHMOND DEPARTMENT OF PUBLIC WORKS AND IMPACTED PROPERTY OWNERS.

ALL AREAS EXCAVATED DEEPER THAN 2" BELOW EXISTING PAVEMENT SURFACE AND WITHIN THE CLEAR ZONE. AT THE CONCLUSION OF EACH WORKDAY, SHALL BE BACK FILLED TO FORM AN APPROXIMATE 6:1 WEDGE AGAINST THE PAVEMENT SURFACE FOR THE SAFETY AND PROTECTION OF VEHICULAR TRAFFIC. ALL COST OF PLACING, MAINTAINING AND REMOVING THE 6:1 WEDGE SHALL BE INCLUDED IN THE PRICE BID FOR OTHER ITEMS IN THE CONTRACT AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED. THIS APPLIES ONLY TO THE CONNECTION POINTS AT DEEPWATER TERMINAL ROAD AND GOODES STREET WHERE TRAFFIC IS PRESENT.

6. LANE CLOSURES WILL NOT BE PERMITTED ON HOLIDAYS OR WEEKENDS UNLESS OTHERWISE APPROVED IN ADVANCE BY THE CITY OF RICHMOND DEPARTMENT OF PUBLIC WORKS.

Typical Traffic Control Shoulder Operation with Minor Encroachment (Figure TTC-5.1) NOTES

April 2015

Page 6H-68

April 2015

1. For required sign assemblies for multi-lane roadways see Note 1, TTC-4.1 2. Sign spacing should be 1300'-1500' for Limited Access highways. For all other roadways, the sign

April 2015

Typical Traffic Control

Stationary Operation on a Shoulder

(Figure TTC-4.1)

NOTES

1. For long-term stationary work (more than 3 days) on divided highways having a median wider

closed and a RIGHT SHOULDER CLOSED (W21-5aR)1 sign shall be added to that side.

the posted speed limit is 45 mph or less.

2. Sign spacing should be 1300'-1500' for Limited Access highways. For all other roadways, the sign

3. The SHOULDER WORK (W21-5) sign on an intersecting roadway may be omitted where drivers

emerging from that roadway will encounter another advance warning sign prior to this activity area.

4. For short duration operations of 60 minutes or less, all signs and channelizing devices may be

5. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity amber

7. The buffer space length shall be as shown in Table 6H-3 on Page 6H-5 for the posted speed limit.

8. A truck-mounted attenuator (TMA) shall be used on the shadow vehicle on Limited Access

9. When a side road intersects the highway within the temporary traffic control zone, additional

Stationary Operation on a Shoulder

(Figure TTC-4.1)

highways and multi-lane roadways with posted speed limit equal to or greater than 45 mph for

high-intensity amber rotating, flashing, or oscillating, lights.

Lane Width (Feet)

9 10 11 12

Taper Length (L)

25 95 105 115 125

35 185 205 225 245

55 495 550 605 660

65 585 650 715 780

Minimum taper lengths for Limited Access

highways shall be 1000 feet.

operations with a duration greater than 60 minutes.

traffic control devices shall be placed as needed.

April 2015

Shoulder Taper = 1/3 L Minimum

6. Taper length (L) and channelizing device spacing shall be at the following

eliminated if a vehicle with activated high-intensity amber rotating, flashing, or oscillating lights is

rotating, flashing, or oscillating lights. Vehicle hazard warning signals can be used to supplement

Channelizing Device Spacing

Fransition Spacing 20' 40'

onstruction Access* 80' 120'

but shall not exceed one access per 1/4 mile

width of 8 feet or more, channelizing device

shall be used to close the shoulder in

vehicular traffic to remain within the traveled

Spacing may be increased to this distance

on roadways with paved shoulders having a

velway Spacing

Speed Limit (mph

0 - 35 36 +

Page 6H-15

April 2015

than 8', sign assemblies on both sides of the roadway shall be required as shown (ROAD WORK

AHEAD (W20-1), RIGHT SHOULDER CLOSED AHEAD (W21-5bR), RIGHT SHOULDER

CLOSED (W21-5aR)¹), even though only one shoulder is being closed. For operations less than 3

days in duration, sign assemblies will only be required on the side where the shoulder is being

spacing should be 500'-800' where the posted speed limit is greater than 45 mph, and 350'-500' where

Page 6H-16

spacing should be 500'-800' where the posted speed limit is greater than 45 mph, and 350'-500' where the posted speed limit is 45 mph or less. 3. When work takes up part of a lane on a high volume roadway; vehicular traffic volumes, vehicle mix, speed and capacity should be analyzed to determine whether the affected lane should be closed. Unless the lane encroachment analysis permits a remaining lane width of 10 feet, the lane should be closed. If

4. The ROAD WORK AHEAD (W20-1) sign on an intersecting roadway may be omitted where drivers emerging from that roadway will encounter another advance warning sign prior to this activity area.

the closure operation is on a Limited Access highway, the minimum lane width is 11 feet.

5. A shadow vehicle with either an arrow board operating in the caution mode, or at least one highintensity amber rotating, flashing, or oscillating light shall be parked 80' - 120' in advance of the first work crew.

6. Vehicle beyond warning signals shall not be used instead of the vehicle's high-intensity amber rotating, flashing, or oscillating lights. Vehicle hazard warning signals can be used to supplement high-intensity amber rotating, flashing, or oscillating lights.

7. Taper length (L) and channelizing device spacing shall be at the following

T	aper Le	ngth (L	.)		Channelizing Device Spacing			
peed Limit	L	ane Wid	dth (Fee	et)	1 41	Speed Li	mit	
(mph)	9	10	11	12	Location	0 - 35		
25	95	105	115	125	Transition Spacing	20'		
30	135	150	165	180	Travelway Spacing	40'		
35	185	205	225	245	Construction Access*	80'		
40	240	270	295	320	* Spacing may be incre	ased to this	dis	
45	405	450	495	540	but shall not exceed or			
50	450	500	550	600	On roadways with pave			
55	495	550	605	660	width of 8 feet or more, shall be used to clo			
60	540	600	660	720	advance of the merg			
65	585	650	715	780	vehicular traffic to rema	in within t	he t	
70	630	700	770	840	way.			
Minimum tape highwa		ns for Lin be 100		ccess				
Shoulde	r Taper	= ½ L N	linimum					

8. The buffer space length shall be as shown in Table 6H-3 on Page 6H-5 for the posted speed limit. 9. A truck-mounted attenuator (TMA) shall be used on Limited Access highways and multi-lane

roadways with posted speed limit equal to or greater than 45 mph. 10. When a side road intersects the highway within the temporary traffic control zone, additional traffic control devices shall be placed as needed

Shoulder Operation with Minor Encroachment

Typical Traffic Control Flagging Operation on a Single Lane Roundabout (Figure TTC-31.1) NOTES

1. Each roundabout is unique and the traffic control must be developed to meet the specific conditions of the location and the work operation. A detour could possibly better serve traffic movement and must be consider as an alternative to the flagger operation. This traffic control layout can be used on a traffic

April 2015

Page 6H-69

April 2015

Page 6H-102

2. Flaggers shall control traffic flow on all approaches of the one-lane roundabout 3. All flaggers shall be state certified and have their certification card in their possession when performing flagging duties. A lead flagger shall be designated and radio communication shall be

used by the flaggers. 4. Only one quadrant of traffic shall be released at a time.

5. Channelizing device spacing shall be as shown in Note 4 in TTC 32.0. 6. At night, flagger stations shall be illuminated, except in emergencies. Street lights and vehicle

headlights shall not be used to illuminate the flagger station 7. A shadow vehicle with at least one amber high intensity rotating, oscillating, or flashing light shall be parked 80'-120' in advance of the first work crew.

8. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity amber rotating, flashing, or oscillating lights. Vehicle hazard warning signals can be used to supplement high-intensity amber rotating, flashing, or oscillating lights.

9. A minimum of four (4) drum channelizing devices shall be placed on the shoulder in advance of the PCMS in a taper for delineation (see Figure 6F-6).

10. Sign spacing distance should be 350'- 500' where the posted speed limit is 45 mph or less, and 500'-800' where the posted speed limit is greater than 45 mph. 11. A PCMS should be considered as part of the traffic control plan to provide clear guidance to motorist

on all approaches of the roundabout. 12. Care should be exercised when establishing the limits of the work zone to ensure maximum possible sight distance to the flagger station, based on the posted speed limit and at least equal to or greater than the values in Table 6H-3. Generally speaking, motorists should have a clear line of sight from the graphic flagger symbol sign to the flagger.

13. When designing the traffic control and installing the channelizing devices for work activities at roundabouts, accommodations for the turning radius of tractor trailer vehicles and other large vehicles should be considered and the work zone designed accordingly.

14. Periodic adjustments to the channelizing devices may be allowed in an active work zone to 15. A supplemental flagger may be used in the roundabout island to help direct traffic and may be required on the approaches in advance warning of the flagging operation to slow traffic prior to reaching the

16. A guide sign with road names may be used in lieu of the Double Arrow (W12-1) sign. 17. On the approaches where traffic flow will be split, two pilot vehicles may be used to guide traffic

18. Flagging operations may not be necessary when working on the shoulders or in the island of the roundabout. Necessary signage under other typical application must be followed.

Flagging Operation on a Single Lane Roundabout

(Figure TTC-31.1)

Typical Traffic Control Road Closure Operation with a Detour (Figure TTC-48.1)

1. Regulatory traffic control devices should be modified as needed for the duration of the detour. 2. Sign spacing distance should be 500'-800' where the posted speed limit is greater than 45 mph, and 350'-500' where the posted speed limit is 45 mph or less. The directional sign should be placed at the

3. If the road is opened for some distance beyond the intersection and/or there are significant origin/destination points beyond the intersection, the ROAD CLOSED LOCAL TRAFFIC ONLY (R11-3a) and DETOUR (M4-10) signs on Type 3 Barricades should be located at the corners of intersecting closed roadway or the traveled way.

April 2015

Page 6H-112

4. If the road is open for some distance beyond the intersection the Route Sign Directional assembly may be placed in the travelway as shown to augment or replace the one shown on the corners. 5. Flashing warning lights and/or flags may be used to call attention to the advance warning signs.

Cardinal direction plaques may be used with route signs. 7. On divided highways having a median wider than 8', right and left sign assemblies shall be

8. For short-term duration work the M4-9 or M4-V4 series of signs shall be used. For long-term duration work the route shield assembly shall be used with the detour sign.

9. Long-term detours may be signed with a street name (M4-VP1a or M4-Vp1b) plaque above the DETOUR (M4-9 or M4-V4 series) sign (see Figure TTC-34

10. See Chapter 6I for additional information on incident management traffic control

11. Temporary barrier should be placed at a 45° angle to the travelway a sufficient distance beyond the Type 3 Barricade but before the work space while providing equipment access to the work space

12. Barrier panels 8 inches in width and 12 inches in height shall be placed on top of the temporary concrete barrier, perpendicular to traffic, and spaced 20' on centers along the taper sections. Reflectorized surface shall be fluorescent orange prismatic lens sheeting. Barrier delineators shall be installed along the traffic side of the concrete barrier in-between and at the same spacing as the

13. An END DETOUR (M4-8a) sign shall be used with a Cardinal Route shiel and a Cardinal Directional sign to terminate the detour route.

barrier panels approximately 24 inches up from the roadway surface.

Typical Traffic Control Signing for Project Limits (Figure TTC-53.0) NOTES

1. This layout depicts signing requirements for notifying motorist when they are entering and exiting a potential construction/maintenance area with a duration equal to or greater than 60 days.

August 2011

2. The ROAD WORK AHEAD (W20-1) sign or the ROAD WORK NEXT XX MILES (G20-1 (V))

sign shall be placed far enough in advance of the project limits so that other warning signs in a

series may be adequately placed prior to the condition they are warning about. 3. The ROAD WORK NEXT XX MILES sign shall be used for projects with activity areas greater than 2 miles in length, or when multiple work activities (such as pavement patching, guardrail

installations, shoulder restoration, etc.) occur along a highway. 4. The distance displayed on the ROAD WORK NEXT XX MILES sign shall be stated to the nearest


whole mile from the point of installation to the END ROAD WORK (G20-2 (V)) sign. 5. On divided highways having a median wider than 8', right and left sign assemblies shall be


Guidance:


6. For projects with activity areas 2 miles or less in length, the ROAD WORK AHEAD sign should be the 7. Sign spacing should be 1300'-1500' for Limited Access highways. For all other roadways, the sign spacing should be 500'-800' where the posted speed limit is greater than 45 mph, and 350'-500' where

the posted speed limit is 45 mph or less.

8. All connections within the project limits should be identified with signs indicating to motorist they are entering or exiting a potential construction/maintenance area.









Basin Curb & Gutter

Page 6H-14





TIMMONS GROUP .****

. Lot dimensions in parentheses are from deed 2. Property owners correct as of <u>March</u>, 2015 3. Ordinance Number<u>N/A</u> ł. Adopted<u>N/A</u> 5. Accepted<u>N/A</u>

REFERENCES

=======

Castings: Water Valve Water Meter

Technical Marvin Anderson Surveys Superintend Chris Kiefer (Timmons Group) Maritza Feliz-Reyes (DPW) Kenneth D. Horak Maintenance Enginee Michael B. Sawyer City Traffic Engine

Administrative Lamont L. Benjamin Capital Project Administrato Deputy Director for Transportation / Public Wor Bobby Vincent Jr. Emmanuel O. Adediran Director of Public Works

DESIGN BY: M. FLEMING REVIEWED BY DRAWN BY: M. FLEMING CHECKED BY: C. KIEFER

MANAGEMENT PLAN

11/06/15

Proposed Curb Cut Ramp


DEPARTMENT OF PUBLIC WORKS RICHMOND, VIRGINIA


FB-XX, pp XX-XX

HORIZ. N/A

BELMONT ROAD ROUNDABOUT

TRAFFIC PLAN





Water Meter

Gas DripGas Valve

Proposed Curb Cut Ramp

Decorative Light
Conduit
Conduit (Conc. Encased)
Retaining Wall

Chris Kiefer (Timmons Group)

Maritza Feliz-Reyes (DPW)

Kenneth D. Horak

Michael B. Sawyer

Lamont L. Benjamin

Bobby Vincent Jr.

Emmanuel O. Adediran

laintenance Enginee

City Traffic Engine

DEPARTMENT OF PUBLIC WORKS

RICHMOND, VIRGINIA

Capital Project Administrato

Deputy Director for Transportation / Public Work

Director of Public Works

. Property owners correct as of <u>March</u>, 2015

. Ordinance Number<u>N/A</u>

. Adopted<u>N/A</u>

. Accepted N/A

REFERENCES

Storm Sewer Sewer Manhole Sanitary Sewer (Gravity) Sanitary Sewer (Force Mai

Water Line
Tree / Exist. Tree To Be Removed

SAN - -

— FM → — —


⇔ / ※

Proposed Sewer
Manhole
Basin
Curb & Gutter
Asphalt

Lic. No. 23346

302


 SLOPE TO DRAIN TO INVERT OF OUTLET PIPE METHOD OF TREATMENT IN DROP INLETS OUTLET PIPE SECTION B-B METHOD OF TREATMENT IN MANHOLES SPECIFICATION REFERENCE





BELMONT ROAD ROUNDABOUT CONSTRUCTION DETAILS

DESIGN BY: M. FLEMING DRAWN BY: M. FLEMING CHECKED BY: C. KIEFER HORIZ. N.T.S. FB-XX, pp XX-XX

11/06/15











Lic. No. 23346

11/06/15











C. KIEFER
M. FLEMING

SURVEYED BY SUPERVISED I DESIGNED BY





Water Meter


Gas DripGas Valve


RÎCHMOND	
\	
VIRGINIA	
ZIGINII	


Technic	cal	Admini	strative
Marvin Anderson	Surveys Superintendent		
Chris Kiefer (Timmons Group) Maritza Feliz-Reyes (DPW)	Project Engineer	Lamont L. Benjamin	Capital Project Administrator
Kenneth D. Horak	Maintenance Engineer	Bobby Vincent Jr.	Deputy Director for Transportation / Public Works
Michael B. Sawyer	City Traffic Engineer	Emmanuel O. Adediran	Director of Public Works
	DEPARTMENT OF	PUBLIC WORKS	
	RICHMOND,	VIRGINIA	

BELMONT ROAD ROUNDABOUT CONSTRUCTION DETAILS

DESIGN BY: M. FLEMING DRAWN BY: M. FLEMING CHECKED BY: C. KIEFER HORIZ. N/A FB-XX, pp XX-XX 11/06/15











CG-3 MODIFIED

FOR USE ON ROUNDABOUT TRUCK APRONS ONLY










SURVEYED BY: SUPERVISED BY:....



MH-1

HALF PLAN VIEW

4'-8"+ (2 x WALL THICKNESS)




	Techni	cal
	Marvin Anderson	Surveys S
OND\	Chris Kiefer (Timmons Group) Maritza Feliz-Reyes (DPW)	Pro
	Kenneth D. Horak	Maintens
	Michael B. Sawyer	City Tre
		DEPARTM

Technical		Admin	istrative	
Marvin Anderson	Surveys Superintendent			
Chris Kiefer (Timmons Group) Maritza Feliz-Reyes (DPW)	Project Engineer	Lamont L. Benjamin	Capital Project Administrator	
Kenneth D. Horak	Maintenance Engineer	Bobby Vincent Jr.	Deputy Director for Transportation / Public Works	
Michael B. Sawyer	City Traffic Engineer	Emmanuel O. Adediran	Director of Public Works	
	DEPARTMENT OF RICHMOND,			DESIGN BY: DRAWN BY: CHECKED BY:

BELMONT ROAD ROUNDABOUT CONSTRUCTION DETAILS

: 1 : 1 3Y: (M. FLEMING M. FLEMING C. KIEFER	REVIEWED BY	FIELD NOTES FB-XX, pp XX-XX	SCALE HORIZ. N/A VERT. –	DATE 11/06/15	SHEET 2C(3)	0 - 28661



SIGN SCHEDULE

			S	IGN ASS	SEMBLY NENTS		SIGN F	PANEL A (s.f.)						S	IGN ASS	EMBLY NENTS		SIGN I	PANEL A (s.f.)			
TEXT NO.	SIGN ASSEMBLY	TEXT	MUTCD ST'D.	PANE	L SIZE	QTY.	per ASSEMBLY	LL SEM-	PROP. SIGN STRUCTURE ST'D.	REMARKS	TEXT NO.	SIGN ASSEMBLY	TEXT	MUTCD	PANEL	L SIZE	QTY.	per ASSEMBLY	LL SEM- IES	PROP. SIGN STRUCTURE ST'D.		REMARKS
NO.	ASSEMBLY NO(s).		ST'D.	W	Н		ASSE	ASS BL	ST'D.		NO.	NO(s).		ST'D.	W	Н		ASSE	ASS BL	ST'D.		TALIWA KARO
+				·				·											·			
1	101	YIELD	R1-2	36"	36"	4	9	36	STP-1		+ 7	107	LANE ENDS MERGE	W9-2L	36"	36"	2	9	18	STP-1		
+													LEFT			·						
	102		R4-7	36"	48"	2	12	24	STP-1									·			·	
+ .											+ 8	108	20 MPH	W13-1P	18"	18"	4	2.3	9.2	STP-1		
-											-			·							·	
+																·						
			W11-2	30"	30"	Q	6.3	31.5	STP-1													
+ 3	103		W16-7P		12"	8	2	10	011-1													
+ .											+											
<u> </u>											+		· ·									
																·			·			
+ :																						
+ 4	104		W4-2	36"	36"	2	9	18	STP-1													
+ .											+ .									·		
																				·	·	
	105		R6-4	30"	24"		5	20	STP-1					·	·		·		·	·	·	
	103		1.0-4	30	24	4		20	317-1											·		
																·	·		·	·		
+											+ .											
- 6	106		W2-6	30"	30"	4	6.3	25.2	STP-1													
			W16-12P	24"	18"	4	3	12														
		TRAFFIC									+ .											
NOTES:																·						
INVILU.											ı		1	1		1	1	1		ı		

NOTES

SURVEYED BY: TIMMONS GROUP SUPERVISED BY: C. KIEFER DESIGNED BY: M. FLEMING

- 1) ALL SIGNS SHALL BE ORIENTATED AS SHOWN ON THE PLANS.
- 2) SIGN COLOR COMBINATIONS SHALL BE IN ACCORDANCE WITH THE FHWA SHS BOOK AND THE 2011 VIRGINIA SHS BOOK OR AS NOTED IN THE PLANS.
- 3) ALL BLACK SHEETING SHALL BE NON-REFLECTIVE.
- 4) SIGN STRUCTURES SHALL BE INSTALLED PER THE NOTED SIGN ST'D.
- 5) ALL ST'D. STP-1 STRUCTURES TO BE SINGLE POST UNLESS OTHERWISE NOTED.

TIMMONS GROUP .***

NOTES	Existi
1. Lot dimensions in parentheses are from deed.	,
2. Property owners correct as of <u>March</u> , 2015	*
3. Ordinance Number N/A	*
4. Adopted N/A	» »
5. Accepted N/A	*
DEPENDENCIAS DESTICIONS	*


		= =	-:LEGEND:-	~			J. 20 (10 10 10 10 10 10 10 10 10 10 10 10 10 1
& Gutter	=====	= = Exis	sting Curb Cut Ramp	∇_{Λ}	•	Conc. Sidewalk	KXXXXXXXX
ralk		= = .	Coping			Truck Apron	<i>>>>>></i>
l			Alley Crossing/Drivew	ay	Castings:	Water Valve	8
n Sewer	========	===	Fire Hydrant	-6-	* .	Water Meter	•
r Manhole	O		Edge of Pavement			Gas Drip	1 201
ary Sewer (Gravity)	SAN		Fence	x	*	Gas Valve	0
ary Sewer (Force Metr	FM		Cornerstone			Telephone Manhole	(Ť)
Line	— — G— —		Property Pin		*	Electric Manhole	Ď
ric Line	UGP		Utility Pole	Ø	Proposed	Curb Cut Ramp	ĭ ⊗
hone/Telegraph	UGT	Pro	posed Sewer		1100000	our b out manip	
able	— — — UCATV—— -		Manhole	©		Decorative Light	← □
r Line			Basin	<u></u>		Conduit	
/ Exist. Tree To	Be Removed	\$\$ / % \$.	Curb & Gutter			Conduit (Conc. Enc	ased) ====
ambur Tima			Agnhalt			Determine Well	


RÎCHMOND	
IRGINIA	


Technic	eal	Admini	istrative	
Marvin Anderson	Surveys Superintendent			
Chris Kiefer (Timmons Group) Maritza Feliz-Reyes (DPW)	Project Engineer	Lamont L. Benjamin	Capital Project Administrator	
Kenneth D. Horak	Maintenance Engineer	Bobby Vincent Jr.	Deputy Director for Transportation / Public Works	
Michael B. Sawyer	City Traffic Engineer	Emmanuel O. Adediran	Director of Public Works	
	DEPARTMENT OF RICHMOND,			DESIGN BY: DRAWN BY: CHECKED BY

BELMONT ROAD ROUNDABOUT SIGN SCHEDULE

BY: BY: ED BY:	N. BEASLEY T. BUCKLEY N. BEASLEY	REVIEWED BY	FIELD NOTES FB-XX, pp XX-XX	SCALE HORIZ: N/A VERT. —	DATE 11/06/15	2K(2)	0-28661
		•					







SURVEYED BY: SUPERVISED BY DESIGNED BY:..

Lot dimensions in parentheses are from deed.

Property owners correct as of <u>March</u>. 2015

3. Ordinance Number<u>N/A</u>

. Adopted<u>N/A</u>

i. Accepted<u>N/A</u>

REFERENCES

HEIGHT VARIES WITH PLANTS

12" MIN.

GROUNDCOVER/ PERENNIAL PLANTING

PLAN VIEW:

EDGE OF BUILDING,

VOIDS

MULCH LINE

PLANT PERIMETER

WALK OR STRUCTURE

— PLANT UNDER DRIP LINE OF LIMBED UP SHRUBS & TREES

TRIANGULAR INFILL SPACING

PLANT UP TO EDGE OF SHRUBS

UNLESS OTHERWISE NOTED

2-3" MULCH LAYER

1" COMPOST LAYER

- AMENDED SOIL MIX

- UNDISTURBED EARTH

GENERAL NOTES

PRE-CONSTRUCTION

- CONTRACTOR IS RESPONSIBLE FOR CONTACTING "MISS UTILITY" AT 1.800.552.7001 FOR LOCATION OF ALL UTILITY LINES.TREES SHALL BE LOCATED A MINIMUM OF 5 FEET FROM SEWER/WATER CONNECTIONS. NOTIFY LANDSCAPE ARCHITECT OF CONFLICTS.
- VERIFY ALL PLANT MATERIAL QUANTITIES ON THE PLAN PRIOR TO BIDDING, PLANT LIST TOTALS ARE FOR CONVENIENCE ONLY AND SHALL BE VERIFIED PRIOR TO BIDDING.
- PROVIDE PLANT MATERIALS OF QUANTITY, SIZE, GENUS, SPECIES, AND VARIETY INDICATED ON PLANS. ALL PLANT MATERIALS AND INSTALLATION SHALL COMPLY WITH RECOMMENDATIONS AND REQUIREMENTS OF ANSI Z60.1 "AMERICAN STANDARD FOR NURSERY STOCK". IF SPECIFIED PLANT MATERIAL IS NOT OBTAINABLE, SUBMIT PROOF OF NON AVAILABILITY TO THE ARCHITECTS, TOGETHER WITH PROPOSAL FOR USE OF EQUIVALENT MATERIAL.
- PROVIDE AND INSTALL ALL PLANTS AS IN ACCORDANCE WITH DETAILS AND CONTRACT SPECIFICATIONS


CONSTRUCTION/INSTALLATION


- LANDSCAPE ARCHITECT RESERVES THE RIGHT TO REJECT ANY PLANTS AND MATERIALS THAT ARE IN AN UNHEALTHY OR UNSIGHTLY CONDITION, AS WELL AS PLANTS AND MATERIALS THAT DO NOT
- CONFORM TO ANSI Z60.1 "AMERICAN STANDARD FOR NURSERY STOCK" LABEL AT LEAST ONE TREE AND ONE SHRUB OF EACH VARIETY AND CALIPER WITH A SECURELY ATTACHED, WATERPROOF TAG BEARING
- THE DESIGNATION OF BOTANICAL AND COMMON NAME. INSTALL LANDSCAPE PLANTINGS AT ENTRANCES/EXITS AND PARKING AREAS ACCORDING TO PLANS SO THAT MATERIALS WILL NOT INTERFERE WITH SIGHT DISTANCES.
- CONTRACTOR IS RESPONSIBLE FOR WATERING ALL PLANT MATERIAL DURING INSTALLATION AND UNTIL FINAL INSPECTION AND ACCEPTANCE BY OWNER. CONTRACTOR SHALL NOTIFY OWNER OF CONDITIONS WHICH AFFECTS THE GUARANTEE.

INSPECTIONS/GUARANTEE

- UPON COMPLETION OF LANDSCAPE INSTALLATION, THE LANDSCAPE CONTRACTOR SHALL NOTIFY THE GENERAL CONTRACTOR WHO WILL VERIFY COMPLETENESS, INCLUDING THE REPLACEMENT OF ALL DEAD PLANT MATERIAL. CONTRACTOR IS RESPONSIBLE FOR SCHEDULING A FINAL INSPECTION BY THE LANDSCAPE ARCHITECT.
- ALL EXTERIOR PLANT MATERIALS SHALL BE GUARANTEED FOR ONE FULL YEAR AFTER DATE OF FINAL INSPECTION AGAINST DEFECTS INCLUDING DEATH AND UNSATISFACTORY GROWTH. DEFECTS RESULTING FROM NEGLECT BY THE OWNER, ABUSE OR DAMAGE BY OTHERS, OR UNUSUAL PHENOMENA OR INCIDENTS WHICH ARE BEYOND THE CONTRACTORS CONTROL ARE NOT THE RESPONSIBILITY OF THE CONTRACTOR
- PLANT MATERIAL QUANTITIES AND SIZES WILL BE INSPECTED FOR COMPLIANCE WITH APPROVED PLANS BY A SITE PLAN REVIEW AGENT OF THE PLANNING DEPARTMENT PRIOR TO THE RELEASE OF THE CERTIFICATE OF OCCUPANCY.
- REMOVE ALL GUY WIRES AND STAKES 12 MONTHS AFTER INSTALLATION

TREES	QTY	BOTANICAL NAME	COMMON NAME	MINIMUM INSTALLED SIZE	ROOT	REMARKS
ILE MAR	1	llex x `Mary Nell`	Mary Nell Holly	10` Ht	B&B	SPECIMEN
			•			•
SHRUBS	QTY	BOTANICAL NAME	COMMON NAME	MINIMUM INSTALLED SIZE	ROOT	SPACING
ILE CAR	12	Ilex cornuta 'Carissa'	Carissa Holly	18" Sprd	Container	3` O.C.
ILE BUR	13	Ilex cornuta `Dwarf Burford`	Dwarf Burford Holly	24" Ht.	Container	5` O.C.
JUN BLU	339	Juniperus conferta `Blue Pacific`	Blue Pacific Juniper	1 Gal.	Container	2` O.C.
BULBS	QTY	BOTANICAL NAME	COMMON NAME	MINIMUM INSTALLED SIZE	ROOT	SPACING
NAR CAR	443	Narcissus x `Carlton`	Daffodil	BULB	Bulb	2 @ 1 SQ. FT.
			•			•
PERENNIALS	QTY	BOTANICAL NAME	COMMON NAME	MINIMUM INSTALLED SIZE	ROOT	SPACING
HEM BUT	265	Hemerocallis x `Buttered Popcorn`	Daylily	2-1/4" Container	Container	24" O.C.
HEM FIR	265	Hemerocallis x `Fire King`	Daylily	2-1/4" Container	Container	24" O.C.





NOTE: STAKE EVERGREENS 6' OR

CROWNS, OR IF LOCATED ON

WINDY SITES.

TALLER, ON SLOPES, WITH LARGE



PRUNE CODOMINATE LEADERS

GALVANIZED WIRE GUY

RUBBER HOSE

Lic. No. 1628

11/06/15

SHRUB PLANTING

NOT TO SCALE

RÎCHMOND\	
No.	
IRGINIA	

Technic	al	Administrative			
Marvin Anderson	Surveys Superintendent				
Chris Kiefer (Timmons Group) Maritza Feliz-Reyes (DPW)	Project Engineer	Lamont L. Benjamin	Capital Project Administrator		
Kenneth D. Horak	Maintenance Engineer	Bobby Vincent Jr.	Deputy Director for Transportation / Public Works		
Michael B. Sawyer	City Traffic Engineer	Emmanuel O. Adediran	Director of Public Works		
	DEPARTMENT OF	PUBLIC WORKS			

RICHMOND, VIRGINIA

BELMONT ROAD ROUNDABOUT LANDSCAPE NOTES AND DETAILS

CONIFEROUS TREE - STAKING SPECIFIED

DESIGN BY: N. BEASLEY DRAWN BY: T. BUCKLEY CHECKED BY: N. BEASLEY	REVIEWED BY	FIELD NOTES FB-XX, pp XX-XX	SCALE HORIZ. 1" =25' VERT. —	DATE 11/06/15	6(3)	0-28661

